

Recycled Content

Panel | Acoustic

Dashing 1204

Dashing 1204

Panel | Acoustic

Specifications

Content	92% post-consumer recycled polyester 8% pre-consumer recycled polyester
Weight	10.9 ± 1.0 oz./lin. yd 199 g/m ² (± 5%)
Width	66" min. useable 168 cm min. useable
Repeat	2" vertical 2.4" horizontal
Tackable	yes

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 240 lbf warp and 190 lbf fill
	Flammability ASTM E84 Class I or A

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 85%

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

Proudly woven in North America supporting our local communities.

Sustainability

100% recycled and recyclable

Polished Slate
1044

Refined Marble
1042

Antique Sage
1045

Classic Silver
1041

Genteel Beige
1043

Bespoke Tan
1046

duvaltex

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit duvaltex.com

