

Panel

Dune 4505

Seagrass
7109

White
8888

Cloudburst
6701

Breeze
1280

Sandbar
6700

Haze
1203

Clear Sky
1210

Windblown
1201

Drift
1200

Erosion
1202

Basin
1214

Nectar
1208

Shell
7082

Caribbean
6658

Deep Night
1218

Kamelos
1204

Boardwalk
7110

Raven
1215

Darkness
1220

Dune 4505

Panel | Acoustic

Specifications

Content	100% polyester
Weight	11.0 ± 1.0 oz./lin. yd 198 g/m ² (± 5%)
Width	66" min. useable 168 cm min. useable
Repeat	16.4" vertical 13.9" horizontal
Tackable	yes

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

Proudly woven in North America supporting our local communities.

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 160 lbf warp and 110 lbf fill
	Flammability ASTM E84 Class I or A

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:	85%
------------------------	-----

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

duvaltex

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit duvaltex.com

