

C0 Stain Repellent

Seating

Punch Card 1242




Crimson
1307




Alabaster
1301




Putty
1303



Orange
1308



Crisp
1305




Sky
1306




Navy
1309



Burgundy
1311




Peat
1312



Silver Lining
1304



Cadet
1310



Carbon
1302



Abyss
1313

duvaltex

Punch Card 1242

Seating

Specifications

Content	78% polyester 22% post-consumer recycled polyester
Weight	11.1 ± 1.0 oz./lin. yd
Width	54" min. useable
Repeat	25" vertical 12.5" horizontal
Backing	acrylic backcoating
Treatment	C0 stain repellent

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.

Proudly woven in North America supporting our local communities.

Sustainability



duvaltex

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 280 lbf warp and 230 lbf fill
	Seam Slippage (ASTM D4034) 105 lbf warp and 60 lbf fill
	Pilling Resistance (ASTM D3511) Class 4
	Flammability CA Technical Bulletin 117-2013 Section 1
	Abrasion (ASTM D4157) 100,000 double rubs cotton duck

*Certification Marks owned by the Association for Contract Textiles, Inc.

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit duvaltex.com

