

Recycled Content  
Bleach Cleanable

Panel | Acoustic

# FR701® 2100



 **Guilford of Maine**  
Collection

duvalttex

# FR701® 2100

## Specifications

<b>Content</b>	100% post-consumer recycled polyester
<b>Weight</b>	16.0 ± 1.0 oz./lin. 296 g/m <sup>2</sup> (± 5%)
<b>Width</b>	66" min. useable 168 cm min. useable
<b>Repeat</b>	none
<b>Tackable</b>	yes

## Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

**Bleach Cleanable** - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

## Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a non-directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.






## Sustainability

100% recycled and recyclable

 **Guilford of Maine**  
Collection

Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.

## Performance


-  **Colorfastness to light (AATCC 16.3 Option 3)**  
Grade 4 min. at 40 hours
-  **Colorfastness to crocking (AATCC 8)**  
Grade 4 min. dry & Grade 3 min. wet
-  **Breaking Strength (ASTM D5034)**  
150 lbf min. warp and fill
-  **Flammability**  
ASTM E84 Class I or A  
CAN/ULC-S102.2  
EN 1021-1 Cigarette  
EN 1021-2 Match  
EN 13501-1 Adhered Class B, s1, d0  
Flammability performance may vary depending on the substrate used.
- Abrasion (ASTM D4157)**  
 Wyzenbeek Abrasion Resistance (ASTM D4157)  
100,000 double rubs min. cotton duck  
Martindale Abrasion Resistance (ISO 12947-2)  
90,000 cycles

## Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

**Acoustic Transparency:** 95%

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

Certification Marks owned by the Association for Contract Textiles, Inc.



FC-2100 26/02

USA & INTERNATIONAL | T 800-544-0200  
CANADA | T 418 227-9897  
For samples, visit [t.com">duvaltt.com](http://duvalt<span style=)

duvalttex