


CO Stain Repellent

Seating | Panel | Acoustic


Intuition 4856




Sand
1713




Bisque
1711



Coral
1714




Honey
1716



Viridian
1723




Platinum
1717




Ochre
1718




Sage
1721




Peacock
1722




Slate
1719




Scarlet
1720



Hickory
1715



Admiral
1724



Charcoal
1712

duvaltex

Intuition 4856

Seating | Panel | Acoustic

Specifications

Content	55% post-consumer recycled polyester 34% pre-consumer recycled polyester 11% polyester
Weight	11.9 ± 1.0 oz./lin. yd 269 g/m ² (± 5%)
Width	54" min. useable 137 cm min. useable
Repeat	none
Backing	acrylic backcoating
Treatment	CO stain repellent
Tackable	yes

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

Performance

- Colorfastness to light (AATCC 16.3 Option 3)**
Grade 4 min. at 40 hours
- Colorfastness to crocking (AATCC 8)**
Grade 4 min. dry & Grade 3 min. wet
- Breaking Strength (ASTM D5034)**
210 lbf warp and 200 lbf fill
- Seam Slippage (ASTM D4034)**
30 lbf warp and 45 lbf fill
- Pilling Resistance (ASTM D3511)**
Class 4 min.
- Flammability**
CA Technical Bulletin 117-2013 Section 1
ASTM E84 Class I or A
EN 1021-1 Cigarette
EN 1021-2 Match
EN 13501-1 Adhered Class B, s1, d0
Flammability performance may vary depending on the substrate used.
- Abrasion (ASTM D4157)**
 Wyzenbeek Abrasion Resistance (ASTM D4157)
100,000 double rubs min. cotton duck
Martindale Abrasion Resistance (ISO 12947-2)
17,000 cycles

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 95%

For more detailed results, please consult our website.

This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit duvaltex.com



FC-4856 26/02