

# Whisper 1240



† Suitable for printing

# Whisper 1240

## Specifications

|                  |   |
|------------------|---|
| <b>Content</b>   | 53% post-consumer recycled polyester<br>47% polyester |
| <b>Weight</b>    | 10.9 ± 1.0 oz./lin. yd<br>202 g/m <sup>2</sup> (± 5%) |
| <b>Width</b>     | 66" min. useable<br>168 cm min. useable               |
| <b>Repeat</b>    | none  |
| <b>Treatment</b> | polyester binder                                      |
| <b>Tackable</b>  | yes   |






## Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

## Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

## Performance


|   |  |
|---|--|
|  | <b>Colorfastness to light (AATCC 16.3 Option 3)</b><br>Grade 4 min. at 40 hours  |
|  | <b>Colorfastness to crocking (AATCC 8)</b><br>Grade 4 min. dry & Grade 3 min. wet  |
|  | <b>Breaking Strength (ASTM D5034)</b><br>270 lbf warp and 150 lbf fill   |
|  | <b>Flammability</b><br>ASTM E84 Class I or A<br>EN 1021-1 Cigarette<br>EN 1021-2 Match<br>EN 13501-1 Adhered Class B, s1, d0<br>Flammability performance may vary depending on the substrate used. |
|  | <b>Abrasion (ASTM D4157)</b><br>* Wyzenbeek Abrasion Resistance (ASTM D4157)<br>100,000 double rubs min. cotton duck<br>Martindale Abrasion Resistance (ISO 12947-2)<br>40,000 cycles              |

## Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

**Acoustic Transparency:** 95%

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

\*Certification Marks owned by the Association for Contract Textiles, Inc.

