

Biodegradable*

Seating

Cocoon 2198

Nimbus
227

Overcast
222

Stormcloud
223

Snowfall
221

Tawny
228

Serene
237

Nocturne
224

Lamb
226

Flaxen
231

Mist
236

Embergray
229

Odyssey
238

Raven
225

Madder
232

Maple
233

Loden
239

Cherry Fig
234

Heather
235

Blue Chroma
240

Carob
230

Cocoon 2198

CLEAN IMPACT **TEXTILES**[®]

Specifications

Content	100% post-consumer recycled biodegradable* polyester
Weight	19 ± 1.0 oz./lin. yd 430 g/m² (± 5%)
Width	54" min. useable 137 cm min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.

Sustainability

BIODEGRADABLE* CLEAN IMPACT TEXTILES[®] address the daunting problem of how to deal with polyester fabric at the end of its useful life.

Biodegradable* in landfill after 1,278 days (tested under ASTM D5511)

* Rate and extent of biodegradation into elements found in nature is 91% after 1,278 days under ASTM D5511 (Anaerobic Biodegradation of Plastic Materials Under High Solids Anaerobic Digestion Conditions). The test was done with the same component (PET) polyester and biocatalyst additive. No evidence of further degradation.

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 4 min. wet
	Breaking Strength (ASTM D5034) 195 lbf min. warp and 224 lbf fill
	Seam Slippage (ASTM D4034) 139 lbf min. warp and 132 lbf min. fill
	Pilling Resistance (ASTM D3511) Class 3.5 min.
	Flammability CA Technical Bulletin 117-2013 Section 1 NFPA 260-2013 Class I EN 1021-1 Cigarette EN 1021-2 Match Flammability performance may vary depending on the substrate used.
	Abrasion (ASTM D4157) Wyzenbeek Abrasion Resistance (ASTM D4157) 100,000 double rubs min. cotton duck Martindale Abrasion Resistance (ISO 12947-2) 100,000 cycles

Certification Marks owned by the Association for Contract Textiles, Inc.

