Dune 4505


Seagrass
7109

White
8888


Cloudburst
6701


Breeze
1280


Sandbar
6700


Haze
1203


Clear Sky
1210


Windblown
1201


Drift
1200


Erosion
1202


Basin
1214


Nectar
1208


Shell
7082


Caribbean
6658


Deep Night
1218


Kamelos
1204


Boardwalk
7110


Raven
1215


Darkness
1220

duvaltex

Dune 4505

Panel | Acoustic

Specifications

Content	100% polyester
Weight	11.0 ± 1.0 oz./lin. yd 198 g/m^2 (± 5%)
Width	66" min. useable 168 cm min. useable
Repeat	16.4" vertical | 13.9" horizontal
Tackable	yes

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

Proudly woven in North America supporting our local communities.

Performance

Colorfastness to light (AATCC 16.3 Option 3)
Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

Breaking Strength (ASTM D5034)
160 lbf warp and 110 lbf fill

Flammability
ASTM E84 Class I or A

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:	85%

For more detailed results, please consult our website.

This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

duvaltex

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit **duvaltex.com**

FC-4505 **26/08**