

Felt 9900

Felt 9900

Specifications

Content	80% polyester 20% post-consumer recycled polyester
Weight	10.2 ± 1.0 oz./lin. yd 189 g/m ² (± 5%)
Width	64" min. useable 162 cm min. useable
Repeat	none
Tackable	yes

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 130 lbf min. warp and 95 lbf min. fill
	Flammability ASTM E84 Class I or A

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:	99%
------------------------	-----

For more detailed results, please consult our website.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a non-directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

*Light fabric are subject to transparency issues depending on lighting intensity and internal structure. Application testing of this product is recommended.

This product is a **Feltväri™** non-woven.

Proudly made in North America supporting our local communities.



® This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

White*
8888

Maize
3204

Dune
3062

Pear
3210

Cherry
3362

Ivory
3206

Aluminum
3055

Liberty
3053

Deep Sea
3054

Pebble
3056

Sterling
3057

Ebony
3059

