

Recycled Content

Seating | Panel | Acoustic

Anchorage 2335 | Open House 2334

White*
2664

Shadow†
6694

Birch
2129

Vanilla
2130

Angora
2035

Asteroid
2053

Goose
2049

Fossil
2093

Graphite
2079

Coffee Bean
2083

Slate
2017

Wolf
2027

Quarry Blue
2026

Lapis
2094

Deep Water
2051

Waterfall
2691

Pool
2842

Thistle
2085

Cobalt
2045

Midnight
2025

Cumin
2050

Eucalyptus
2047

Willow
2028

Green Apple
2087

Fern
2840

Turquoise
2841

Pine Needle
2022

Onyx
2016

Aubergine
2036

Straw
2034

Lemon
2839

Sunshine
2082

Goldenrod
2090

Pumpkin
2021

Geranium
2084

Red Delicious
2014

Poppy
2091

Orchid
2843

Mulberry
2044

*Not recommended for use as Upholstery.

Anchorage 2335 Open House 2334

Seating | Panel | Acoustic

Specifications

Content	65% pre-consumer recycled polyester 35% post-consumer recycled polyester
Weight	2334 - 13.1 ± 1.0 oz./lin. yd 2335 - 15.0 ± 1.0 oz./lin. yd
Width	2334 - 54" min. useable 2335 - 66" min. useable
Repeat	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- Please specify when ordering whether 54" or 66" width is needed. Dye lots may vary. Differences may also occur between corresponding colors of Anchorage 2335 and Open House 2334.

Proudly woven in North America supporting our local communities.





Sustainability

100% recycled and recyclable



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.

Performance


	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 275 lbf min. warp and fill
	Seam Slippage (ASTM D4034) 50 lbf min. warp and fill
	Pilling Resistance (ASTM D3511) Class 4 min.
	Flammability CA Technical Bulletin 117-2013 Section 1 ASTM E84 Class I or A
	Abrasion (ASTM D4157) 250,000 double rubs min. cotton duck

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 85%

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Certification Marks owned by the Association for Contract Textiles, Inc.

†Available in 66" only.

duvaltex

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit [duvaltex.com](https://www.duvaltex.com)