

Recycled Content

Panel | Acoustic

Twweed 2737

Twweed 2737

Panel | Acoustic

Specifications

Content	75% pre-consumer recycled polyester 25% post-consumer recycled polyester
Weight	11.7 ± 1.0 oz./lin. yd 210 g/m ² (± 5%)
Width	66" min. useable 168 cm min. useable
Repeat	none
Tackable	yes

Performance

	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
	Breaking Strength (ASTM D5034) 225 lbf min. warp and 175 lbf fill
	Flammability ASTM E84 Class I or A

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency: 95%

For more detailed results, please consult our website.

Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a directional fabric.
- Tackable properties may vary depending on fabric structure and recovery characteristics.

Proudly woven in North America supporting our local communities.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

Sustainability

100% recycled and recyclable

Twinkle 2168 Concrete 2144

Bleach White 2766 Wheat 2187 Stainless 2195

Metal 2193 Orange 2767 Lipstick 2770 Leaf 2772

Spa 2773 Royal Blue 2771 Java 2197

duvaltex

USA & INTERNATIONAL | T 800-544-0200
CANADA | T 418 227-9897
For samples, visit duvaltex.com

