






PRISM

SPORT-IMPACT INSTALLATION



COMPOSITION

- ① Fabric and color, selected by client
- ② Acoustic structure: 100% Polyester
- ③ Acoustic Lining: Stone wool

PRODUCT INFORMATION

	Dimensions W x H	Thickness	Acoustic Surface Area	Product Code†	Walls & Ceilings	Concealed grid	Baffles*	Clouds*
	24 x 24 in 610 x 610 mm	3 in 76 mm	4 ft ² 0.372 m ²	PRIA-2424-S-X-****-****	●	—	●	●

IMPORTANT - PRISM SPORT-IMPACT tiles can only be installed with ZEN SPORT-IMPACT tiles at the perimeter

Perimeter Moldings



Artotrim-C3
ARTC-3144-M-X-0000-0002

- Perimeter molding for Zen tiles, whole or cut to size, allows for adjustment to the wall.



Artotrim-L4
ARTL-4096-M-X-0000-0002

- Finishing molding for 3/8 in plywood or OSB backing
- Also available: **Artotrim-L1** for plywood and 1/2 in OSB

STANDARD FABRICS

100% polyester (% of recycled fibers varies by fabric)
Intertek Clean Air Gold certified for very low VOC emissions
For available styles, consult our website.

FLAMMABILITY

ASTM-E-84: Class A
CAN/ULC-S102.2

ACOUSTIC PERFORMANCE**

Noise Reduction Coefficient (Hz)
NRC 0.85

†Fabrics

Replace ****-**** with the style number of the fabric, followed by the color number.

*Baffles and Clouds

For available formats, consult the product sheets or visit our website.

TILE LAYOUT

Need to be inspired? Visit our website www.duvaltex.com for more details on our products and possible layouts. You can also contact us or reach out to one of our authorized local distributors.

**Results were determined through testing conducted by an independent, certified laboratory according to industry standards. ASTM C423 - Standard test method for sound absorption coefficients by the reverberation room method. See the Acoustic Performance sheet for more information.

Drawings not to scale. Do not use as template. The information contained in this document is the property of ARTOFIX. Reproduction is prohibited.

duvaltex.com

1-450-646-7555

solutions@duvaltex.com

duvaltex